

PRO-TEC EQUIPMENT MOD SERIES

The Pro-Tec Equipment MOD Series is a modular aluminum trench shield system that is lightweight and easily transported via pick-up truck. It can be used as a 2-, 3- or 4-sided system with existing components and can be changed on the fly at a jobsite to meet the job's requirements.

Standard features:

- Smooth wall panel design
- Foam filling prevents soil and water buildup
- Accepts telescoping spreaders (MTS Spreaders)
- Bottom panels can be removed
- 2-way corner posts allow, 2-, 3- or 4-sided configurations
- Professional Engineer Certified to meet or exceed O.S.H.A. requirements


MOD Series Options

- Aluminum built-in knife edge
- Steel bolt-on knife edge
- Wheel kits
- Adjustable legs
- Lifting eyes
- Stacking units
- Custom sizes

Quick and Easy **Assembly**

1. Attached corner post to one panel, Install pins with handles on the outside.





日





4. Attached 2nd and 3rd corner posts.




5. Stack and slide panels to desired height. Add 4th corner post.



6. Install lift eyes and spreaders in required locations, refer to tabulated data.




Corner Post (2-way)



Model	Length	Weight (lb.)
MC 24	24"	19
MC 48	48"	38
MC 72	72"	56
MC 96	96"	75
MC 120	120"	94

Corner Post (3-way)



Model	Length	Weight (lb.)
MC 3-24	24"	25
MC 3-48	48"	51
MC 3-72	72"	76
MC 3-96	96"	101
MC 3-120	120"	127

MOD Panel Denth Chart


Width	Weight	ht Maximum Depth of Cut (ft.)		
x Lgth (ft.)	(lb.)	В	C -60	C-80
MPS 2 x 3	50	50	50	42
MPS 2 x 4	60	50	42	32
MPS 2 x 6	90	38	28	21
MPS 2 x 8	120	28	21	16
MPS 2 x 10	140	23	17	13
MPS 2 x 12	170	19	14	11
MPS 2 x 14	190	12	9	7

Heavy duty and special length panels are available


Telescoping Adjustable Spreader Sets (set of 4)




Model (Sets of 4)	Adjustment (I.D.)	Weight (lb.)
TS 4 - 1826	18" to 26"	108
TS 4 - 2334	23" to 34"	128
TS 4 - 2844	28" to 44"	153
TS 4 - 3454	34" to 54"	183
TS 4 - 4266	42" to 66"	223
TS 4 - 5288	52" to 88"	273




End View Sectional corner post with adjustable struts



End View
Full length corner post with
adjustable struts



Panels omitted to allow for T-connections or existing utilities



3-way corner post

Adjustable strut

Top View System using 3-way corner post

Adjustable Spreaders (Inside Panel Dimensions)

MOD Panel

2-way corner post

Model	Adjustment	Weight (lb.)
MAS 23	24" to 36"	27
MAS 35	36" to 60"	37
MAS 57	60" to 84"	46
MAS 79	84" to 108"	55





PRO-TEC EQUIPMENT

4837 West Grand River Ave

Lansing, MI 48906 Phone: 1-800-292-1225

Fax: (517) 827-3263

www.pro-tecequipment.com

The information in this brochure is presented in good faith to assist the user in determining whether our products are suitable for his/her application. No warranty or representation, however, is intended or made, nor is protection from any law or patent to be inferred, and all patent rights are reserved. Job site photos are strictly intended for general product information only and may not comply with all applicable safety standards. Always refer to manufacturer's specific tabulated data, O.S.H.A. 29 CFR 1926 Subpart P for excavation and all applicable safety standards prior to each use. ©2019 Pro-Tec Equipment. All rights reserved.

